

---

# Product Design Specification Example Engineering

---

*Product Design  
Specification Example  
Engineering*

*Downloaded from  
[www.whlarchitecture.com](http://www.whlarchitecture.com)  
by Moon & Dayton*

---

## INTRODUCTION: THE BLUEPRINT OF ENGINEERING SUCCESS

---

Every great product begins not with a sketch, but with a document. In the world of engineering, the **Product Design Specification (PDS)** serves as the foundational blueprint that guides a team from concept to completion. Whether you are developing a consumer

electronic, a medical device, or an industrial machine, a well-crafted PDS ensures that every stakeholder—from designers and engineers to marketing and manufacturing—shares a clear, unambiguous understanding of what the product must achieve.

This article explores what a **Product Design Specification example engineering** context looks like, why it matters, and how you can create one that drives efficiency, reduces costly

revisions, and delivers a product that satisfies both user needs and business goals. By the end, you will have a practical framework and a concrete example to apply directly to your next project.

---

## WHAT IS A PRODUCT DESIGN SPECIFICATION (PDS)?

---

A Product Design Specification is a formal document that details the functional, performance, physical, and regulatory requirements of a product. Unlike a vague brief, the PDS provides measurable, testable criteria that every design iteration must meet. In engineering, the PDS bridges the gap between market research and detailed design, ensuring that technical teams do not waste time on features that do not

align with user needs or manufacturing constraints.

The keyword **Product Design Specification example engineering** appears naturally throughout this discussion because understanding a real-world example is the best way to internalize the concept. A PDS typically includes sections such as:

- Purpose and scope
- Functional requirements
- Performance standards
- Physical characteristics (size, weight, materials)
- Environmental conditions (temperature, humidity, vibration)
- Safety and regulatory compliance
- Reliability and durability targets
- User interface and ergonomics

- Cost targets
- Testing and verification methods

Each requirement must be specific, measurable, and achievable. Vague statements like "the device should be durable" are replaced with "the device must withstand 10,000 cycles of operation without failure under normal load."

---

## WHY ENGINEERING TEAMS NEED A PDS

---

Without a detailed PDS, engineering projects often suffer from scope creep, miscommunication, and rework. A clear PDS serves multiple purposes:

1. **Alignment:** It ensures that all team members and departments work toward the same goals.

2. **Decision-making:** When trade-offs are necessary, the PDS provides objective criteria to evaluate options.
3. **Risk reduction:** Identifying requirements early helps avoid late-stage surprises that delay launch.
4. **Validation:** A PDS allows you to test the final product against predefined standards, proving that the design is fit for purpose.
5. **Compliance:** Many industries require documented specifications for regulatory approval (e.g., medical, automotive, aerospace).

For a **Product Design Specification example engineering** team, the PDS is the single source of truth. It lives

alongside drawings and CAD models but is not replaced by them. While a drawing shows the geometry, the PDS explains the "why" behind every dimension and material choice.

---

### **KEY ELEMENTS OF AN ENGINEERING PDS**

---

To illustrate, let us break down what goes into a typical PDS. Each element should be defined with clarity and precision.

## 1. Functional Requirements

What must the product do? These are the primary tasks the product performs.

For example, a coffee maker must heat water to 92–96°C, brew a cup within four minutes, and hold at least 1.5 liters of water. Functional requirements are the non-negotiable core of the design.

## 2. Performance Requirements

How well must it perform? This includes speed, accuracy, capacity, and efficiency. In engineering, performance is often quantified. For instance: "The pump must deliver 5 liters per minute at a head of 10 meters with an efficiency of 75%." These numbers become the benchmarks for success.

### 3. Physical and Interface Requirements

Dimensions, weight, materials, color, texture, and ergonomics fall here. For a handheld device, weight might be critical to user comfort. For a medical device, materials must be biocompatible. Including these early prevents later conflicts with industrial design or manufacturing.

### 4. Environmental and Operating Conditions

Products operate in real-world conditions. Your PDS should specify temperature range, humidity, altitude, exposure to dust or water, and vibration tolerance. For example, "The outdoor sensor must operate between -20°C and 60°C and withstand IP67 water ingress."

### 5. Regulatory

## and Safety Standards

Engineering products often must meet standards like ISO, ASTM, UL, CE, or FDA requirements. List every applicable standard in the PDS. Non-compliance can stop production or lead to liability.

## 6. Reliability and Lifecycle

Define the expected lifespan in hours, cycles, or years. Include failure rates (e.g., MTBF – Mean Time Between Failures) and maintenance intervals. For example: "The actuator must operate for

1,000,000 cycles with less than 5% reduction in torque."

## 7. Cost Targets

Every engineering decision has a cost impact. A PDS often includes a target manufacturing cost (e.g., "Bill of materials must not exceed \$50 per unit at volume 10,000 units/year"). This guides material selection and process choices.

---

### A COMPLETE PRODUCT DESIGN SPECIFICATION EXAMPLE ENGINEERING PROJECT

---

Now let us examine a full **Product Design Specification example engineering** scenario: designing a portable battery-powered water pump

for emergency use. This example will weave the keyword naturally and show how each section comes together.

# Project:

## Emergency Portable Water Pump – PDS v1.0

### 1. PURPOSE AND SCOPE

Develop a hand-portable, battery-operated water pump capable of drawing water from a source up to 5 meters deep and delivering a flow of at least 10 liters per minute for emergency

drinking water supply. The device must be light enough to carry in a backpack and operate in adverse conditions.

### 2. FUNCTIONAL REQUIREMENTS

- The pump must be self-priming up to 4 meters vertically.
- It must operate with a rechargeable lithium-ion battery (12V DC).
- Battery life must provide at least 60 minutes of continuous operation at full flow.
- Must include a user-replaceable pre-filter and output hose connection (standard garden hose thread).

### 3. PERFORMANCE REQUIREMENTS

- Flow rate: 10 liters per minute  $\pm 10\%$  at 1 meter head.
- Maximum head: 8 meters.
- Power consumption:  $\leq 100$  watts at nominal load.
- Battery recharge time:  $\leq 4$  hours from empty with included charger.

### 4. PHYSICAL AND INTERFACE SPECIFICATIONS

- Weight:  $\leq 2.5$  kg including battery.
- Dimensions:  $\leq 30$  cm x 20 cm x 15 cm.
- Housing: Impact-resistant ABS plastic, UV-stable.
- Water inlet: 1-inch diameter flexible hose with quick-connect.
- Outlet: 3/4-inch barbed fitting.

- Color: Safety yellow with high-contrast black button.

### 5. ENVIRONMENTAL CONDITIONS

- Operating temperature: 0°C to 45°C.
- Storage temperature: -10°C to 60°C.
- Water temperature: 5°C to 40°C.
- Ingress protection: IP54 (splash-proof and dust-resistant).
- Must withstand drop from 1 meter onto concrete.

### 6. REGULATORY AND SAFETY STANDARDS

- Compliant with CE marking and RoHS.
- Battery must meet UN38.3 for



transport.

- Electrical safety to EN 60335-2-41 (pumps).
- Food-grade materials for all wetted components per NSF/ANSI 61.
- User manual must include lockout/tagout instructions for battery removal.

## 7. RELIABILITY AND LIFECYCLE

- Design life: 500 operating hours with normal maintenance.
- Mean Time Between Failures (MTBF):  $\geq 2000$  hours at 90% confidence.
- Battery cycle life:  $\geq 300$  charge/discharge cycles to 80% capacity retention.
- Seals must withstand 500 hours of continuous exposure to water

without leakage.

## 8. COST TARGETS

- Target unit manufacturing cost (materials + labor):  $\leq \$45$  at annual volume 50,000 units.
- Battery pack cost:  $\leq \$12$ .
- Mold tooling investment:  $\leq \$150,000$ .

## 9. TESTING AND VERIFICATION

- Flow testing on a calibrated test stand with water at 20°C.
- Drop test at 1 m onto all six faces and four edges.
- Environmental chamber tests at temperature extremes.
- Salt spray test per ASTM B117 for corrosion resistance (48 hours).

- Electrical safety tests per applicable standards.
- Battery discharge profile testing.

## 10. USER EXPERIENCE AND ERGONOMICS

- Single-button start with LED indicators for battery level, on/off, and error.
- Handle design comfortable for hand-carry, with rubber grip.
- Hose connections tool-free.
- Control panel with tactile feedback.
- Battery compartment accessible with coin-turn screw (avoid tools).

This **Product Design Specification example engineering** document gives every team member a clear target. An

engineer can begin CAD work knowing exactly the size and weight constraints. The procurement team can source materials that meet cost targets. Quality assurance can plan tests that directly verify each requirement.

---

### BEST PRACTICES FOR WRITING AN ENGINEERING PDS

---

Creating an effective PDS requires discipline. Follow these guidelines to avoid common pitfalls.

## Involve Cross-Functional

# Stakeholders Early

Do not write the PDS in isolation. Interview marketing, manufacturing, service, and even end users. A requirement that marketing wants may conflict with cost targets; discovering this early lets you trade off consciously.

# Use Measurable Language

Avoid words like "efficient," "fast," or "user-friendly" without defining them. Replace with "efficiency  $\geq 80\%$ ," "startup time  $\leq 2$  seconds," or "button reachable

by 5th percentile female user." Every requirement should be testable by a clear pass/fail criterion.

# Prioritize Requirements

Not all requirements are equal. Use a classification system such as "Mandatory," "Desirable," and "Future." This helps when trade-offs must be made. The PDS for the **Product Design Specification example engineering** above could classify flow rate as mandatory, while color preference maybe desirable.

## Keep the Document Living

A PDS is not static. As the design matures and new insights emerge, update the specification. However, control changes through a revision history. Every change should be signed off by the project manager and key stakeholders to avoid chaos.

## Link to Verification

## Methods

For each requirement, specify how it will be checked. This might be "Design review," "Simulation," "Prototype test," or "Inspection." This closes the loop between specification and quality assurance.

## Include Tolerance Ranges

Perfect numbers are rare. Provide acceptable ranges where appropriate. For example, "weight: 2.5 kg  $\pm$  0.2 kg" gives the team flexibility without

sacrificing the target.

### **COMMON MISTAKES TO AVOID**

Even experienced engineering teams fall into these traps. Here are the most frequent:

- **Over-specification:** Adding too many unnecessary requirements that inflate cost or restrict design innovation.
- **Under-specification:** Leaving out critical performance or environmental conditions, leading to field failures.
- **Contradictory requirements:** For example, "low cost" and "aerospace-grade materials" are often inconsistent. Resolve conflicts explicitly.